

6-LOBE SOLID HANDWHEEL WITH FEMALE THREADED INSERT

6-lobe handwheels

The solid 6-lobe handwheel with insert with female threaded hole has been designed to replace all older solid bakelite handwheels or knobs. The product is "solid", meaning that it has no cavities where dirt can build up. There is only a small recess at the top of the rim, but this recess is very wide and shallow, and therefore easy to clean. This line of knobs is therefore suitable for use on all equipment or machinery that needs to be cleaned or sanitised frequently. It is mainly used on machines used by bakeries, food processing machinery in general, hospital equipment, wheelchairs and medical equipment in general. Of course, it can be chosen simply because it is so robust. The F175 lobe handwheel is made from high-strength reinforced polyamide materials. Available in a range of versions and models (lobe handwheel with through-hole insert, 6-lobe handwheel with steel hub, 6-lobe handwheel with retaining chain, etc.).

Materials:

Reinforced polyamide.

Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black (RAL 9011).

Inserts:

Version F175:

Brass insert with female threaded hole (thread tolerance 6H).

Version F175CIN:


Stainless steel insert with female threaded hole (Aisi 303) (thread tolerance 6H).

Special Requests:

Upon request and for special quantities inserts can be supplied in different materials.

Upon request and for special quantities available in the colours indicated in the chart (attention: reduced range).





Version F175: with brass insert.

Code	Art.	D	H	d	c	m	d3	h3	d1 6H	Q	Weight (g)
F17530.0001	F17530.TM0401	30	22	15	11	11	9	1.5	M4	6	11.5
F17530.0004	F17530.TM0501	30	22	15	11	11	9	1.5	M5	14	11.5
F17530.0010	F17530.TM0601	30	22	15	11	11	9	1.5	M6	10	12
F17530.0018	F17530.TM0801	30	22	15	11	11	9	1.5	M8	14	13.5
F17530.0021	F17530.TM1001	30	22	15	11	11	9	1.5	M10	14	14
F17540.0001	F17540.TM0501	40	24.5	17	12	12.5	12	1	M5	14	22
F17540.0004	F17540.TM0601	40	24.5	17	12	12.5	12	1	M6	18	22
F17540.0010	F17540.TM0801	40	24.5	17	12	12.5	12	1	M8	14	21.5
F17540.0017	F17540.TM1001	40	24.5	17	12	12.5	12	1	M10	14	21
F17550.0003	F17550.TM0601	50	29	20	15,5	13,5	14.5	1.5	M6	16	36
F17550.0006	F17550.TM0801	50	29	20	15,5	14	14.5	1.5	M8	14	36
F17550.0014	F17550.TM1001	50	29	20	15,5	13,5	14.5	1.5	M10	13	37
F17550.0022	F17550.TM1201	50	29	20	15,5	13,5	14.5	1.5	M12	18	39
F17560.0002	F17560.TM0801	60	34	24	16	18	18	1.5	M8	19	59
F17560.0006	F17560.TM1001	60	34	24	16	18	18	1.5	M10	21	59
F17560.0014	F17560.TM1201	60	34	24	16	18	18	1.5	M12	18	62
F17560.0020	F17560.TM1401	60	34	24	16	18	18	1.5	M14	19	63

Version F175CIN: with stainless steel insert (Aisi 303).

Code	Art.	D	H	d	c	m	d3	h3	d1 6H	Q	Weight (g)
F17530.0007	F17530.TM0501CIN	30	22	15	11	11	9	1.5	M5	14	11.5
F17530.0013	F17530.TM0601CIN	30	22	15	11	11	9	1.5	M6	10	12
F17530.0019	F17530.TM0801CIN	30	22	15	11	11	9	1.5	M8	14	13.5
F17540.0007	F17540.TM0601CIN	40	24.5	17	12	12.5	12	1	M6	9	22
F17540.0013	F17540.TM0801CIN	40	24.5	17	12	12.5	12	1	M8	14	21.5
F17540.0018	F17540.TM1001CIN	40	24.5	17	12	12.5	12	1	M10	14	21
F17550.0009	F17550.TM0801CIN	50	29	20	14	15	14.5	1.5	M8	14	36
F17550.0017	F17550.TM1001CIN	50	29	20	14	15	14.5	1.5	M10	14	37
F17550.0023	F17550.TM1201CIN	50	29	20	14	15	14.5	1.5	M12	13	39
F17560.0004	F17560.TM0801CIN	60	34	24	16	18	18	1.5	M8	19	59
F17560.0009	F17560.TM1001CIN	60	34	24	16	18	18	1.5	M10	21	59
F17560.0017	F17560.TM1201CIN	60	34	24	16	18	18	1.5	M12	18	62