

**10**

## UNIVERSAL LOCK FOR 7 MM SQUARE INSERT KEY

1/4 turn locks M19

### Materials:

- (1) Die-cast zamak lock body M19 (stator) and rotor. 7 mm square insert key.
- (2) Elastic washer d. 24x1 with bore d. 19.4.
- (3) Steel hexagon lock nut M19x1.
- (4) Steel locking lever. (Qn design N flat - Qe design E bent outwards).
- (5) Conical steel elastic washer d. 12x1.5.
- (6) Steel Phillips dome head screw M5x8.

### Surface finish:

- (1) Nickel-plated.
- (2-5) Black oxide treated.
- (3-4-6) Standard blue galvanising.

### Key (optional):

- (7) Red plastic key. Art. J09050.TQ0816.

ATTENTION: The key is not supplied. To be ordered separately.

### Rotation:

90°.

### Special Requests:

None.



BOTECO  
Copyright ©



BOTECO  
Copyright ©



| Code        | Art.              | A | d   | D  | L  | Q  | E | F  | G  | Ht | H | s (max.) | s1  | Weight (g) | Key           |
|-------------|-------------------|---|-----|----|----|----|---|----|----|----|---|----------|-----|------------|---------------|
| J14419.0001 | J14419.Z07E00X38L | 7 | M19 | 22 | 38 | 20 | 0 | 16 | 22 | 31 | 4 | 6        | 2,5 | -          | J09050.TQ0816 |
| J14419.0002 | J14419.Z07E02X38L | 7 | M19 | 22 | 38 | 20 | 2 | 16 | 22 | 31 | 4 | 6        | 2,5 | -          | J09050.TQ0816 |
| J14419.0003 | J14419.Z07E05X35L | 7 | M19 | 22 | 35 | 20 | 5 | 16 | 22 | 31 | 4 | 6        | 2,5 | -          | J09050.TQ0816 |
| J14419.0004 | J14419.Z07E09X35L | 7 | M19 | 22 | 35 | 20 | 9 | 16 | 22 | 31 | 4 | 6        | 2,5 | -          | J09050.TQ0816 |