

T-HANDLE WITH THREADED INSERT

T-handles

The T-handle with insert with female threaded hole is designed for two uses: the first and most important, given the design, is the push-pull mode. That is, connected to a shaft and 'pulled' or 'pushed'. The second is a combination of rotation and push/pull. The handle is solid, without cavities, so it is also suitable for the food and medical sector. Several versions of the product are available such as with stainless steel insert or thread on the plastic without insert. Suitable for special uses where a metal-free product is required. Its use is a little more limited than other more universal handles. Indeed, it is mainly used on hand tools, automotive equipment, woodworking machines and a wide range of sports or gym equipment. The L270 T-handle is made from reinforced polyamide based materials. Also available with smooth bore or threaded stud insert.

Materials:

Reinforced polyamide.

Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black: (RAL 9011 code 01).

Orange: (RAL 2004 code 02).

Red: (RAL 3000 code 16).

Inserts:


Brass insert with female threaded hole (thread tolerance 6H).

Special Requests:

Upon request and for special quantities inserts can be supplied in different materials.

Upon request and for special quantities available in the colours indicated in the chart.





Version L270 - 01 Black T-handle (RAL 9001 code 01)

Code	Art.	A	B	H	h1	c	d	d1 6H	Q	Weight (g)	F1 (N)
L27050.0002	L27050.TM0501	50	15	24	17	5	14	M5	12	13	4100
L27050.0009	L27050.TM0601	50	15	24	17	5	14	M6	10	11	4100
L27050.0015	L27050.TM0801	50	15	24	17	5	14	M8	14	12	4100
L27060.0003	L27060.TM0501	60	18	33	24	6	16.5	M5	12	19	5800
L27060.0006	L27060.TM0601	60	18	33	24	6	16.5	M6	10	16.5	5800
L27060.0010	L27060.TM0801	60	18	33	24	6	16.5	M8	14	17.5	5800
L27060.0014	L27060.TM1001	60	18	33	24	6	16.5	M10	21	21	5800
L27072.0003	L27072.TM0601	72	19	34	20	10	18	M6	15	25	6500
L27072.0006	L27072.TM0801	72	19	34	20	10	18	M8	20	28	6500
L27072.0010	L27072.TM1001	72	19	34	20	10	18	M10	21	30	6500
L27072.0017	L27072.TM1201	72	19	34	20	10	18	M12	17	30	6500

Version L270 - 02 Orange T-handle (RAL 2004 code 02)

Code	Art.	A	B	H	h1	c	d	d1 6H	Q	Weight (g)	F1 (N)
L27050.0012	L27050.TM0602	50	15	24	17	5	14	M6	10	11	4100
L27060.0012	L27060.TM0802	60	18	33	24	6	16.5	M8	14	17.5	5800
L27072.0013	L27072.TM1002	72	19	34	20	10	18	M10	21	30	6500

Version L270 - 16 Red T-handle (RAL 3000 code 16)

Code	Art.	A	B	H	h1	c	d	d1 6H	Q	Weight (g)	F1 (N)
L27050.0006	L27050.TM0516	50	15	24	17	5	14	M5	12	13	4100
L27050.0014	L27050.TM0616	50	15	24	17	5	14	M6	10	11	4100
L27060.0013	L27060.TM0816	60	18	33	24	6	16.5	M8	14	17.5	5800
L27072.0015	L27072.TM1016	72	19	34	20	10	18	M10	21	30	6500