

POLYAMIDE / POLYURETHANE WHEEL WITH RECTANGULAR SWIVEL PLATE AND STEEL BEARINGS (HEAVY DUTY SERIES)

Nylon/Polyurethane wheels

Materials:

Wheel body (1):

Polyamide. Resistant to oils and greases.

Tread (2):

Injected polyurethane. Hardness 60 ± 5 Shore D.

Surface finish:

Smooth.

Colour:

(1) Natural white.

(2) Red (Ral 3013).

(3-4-5-6) Galvanised blue.

Wheel rotation (4):

A pair of steel ball bearings is inserted in the wheel hub to provide excellent rollability.

Bracket (3):

Extra-thick steel (DD13) fork.

Rotating assembly (5):

Steel rotating assembly with double ball race, assembled with steel screw grade 8.8 and rectangular swivel plate with four slotted mounting holes.


Wheel fastening (6):

Steel hex head screw, coupled with a self-locking steel nut.

Special requests:

Upon request and for a minimum of 20 pieces, the wheel can be supplied with a needle roller cage, (replace code no. R257 with code no. R247).






 BATECO
 AN ESSENTIA COMPANY
 Copyright ©

Code	art.	D	A	H	I	E	G	M	N	c	h	Weight (g)	F1 (Kg)
R257080.0001	R257080.T34P080X060	80	34	108	47	100	84	80	60	12	9	-	260
R257100.0001	R257100.T40P080X060	100	40	130	47	100	84	80	60	12	9	-	300
R257125.0001	R257125.T40P080X060	125	40	156,5	51	100	84	80	60	12	9	-	400
R257150.0001	R257150.T45P105X080	150	45	195	60	132	110	105	80	23	12	-	600
R257200.0001	R257200.T50P105X080	200	50	242	59	132	110	105	80	23	12	-	700