

18

POLYPROPYLENE / RUBBER WHEEL WITH RIGID STEEL FORK AND SMOOTH THROUGH BORE

PP/Synthetic rubber wheels (institutional)

Materials:

Wheel body:

Polypropylene.

Tread:

Synthetic thermoplastic rubber. Hardness 93 ± 3 Shore A.

Surface finish:

Smooth.

Colour:

(1) Dark grey.

(2) Light grey.

(3-4-5-6-7) Galvanised blue.

Wheel rotation (4):

The hole for the pivot pin is formed by plastic moulding. A galvanised steel tube is positioned between the stud and the hole for protection.

Bracket (3):

Steel (DD13) fork, with mounting hole (hole tolerance H7).

Wheel fastening (6):


Steel hex head screw, coupled with a steel nut.

Special requests:

Upon request the wheel can be supplied in material with high electrical conductivity (ESD).




Copyright ©




BATECO
 AN ESSENTIA COMPANY
 Copyright ©

Code	art.	D	A	H	d	d1 H7	Weight (g)	F1 (Kg)
R610050.0001	R610050.T18D12	50	18	70	48	12	-	40
R610063.0001	R610063.T22D12	63	22	90	48	12	-	60
R610080.0001	R610080.T22D12	80	22	109	48	12	-	60
R610100.0001	R610100.T27D12	100	27	134	57	12	-	80
R610125.0001	R610125.T27D12	125	27	159	57	12	-	80

Code	art.	D	A	H	d	d1 H7	Weight (g)	F1 (Kg)
R610050.0002	R610050.T18D12ESD	50	18	70	48	12	-	40
R610060.0001	R610060.T22D12ESD	60	22	90	48	12	-	60
R610080.0002	R610080.T24D12ESD	80	24	109	48	12	-	60
R610100.0002	R610100.T29D12ESD	100	29	134	57	12	-	80
R610125.0002	R610125.T29D12ESD	125	29	159	57	12	-	80