

22

STAINLESS STEEL COMPLETE KNOB-STYLE SPRING PLUNGER WITH LOCKING POSITION AND STANDARD PITCH THREAD + LOCK NUT

Coarse pitch indexing plungers - full stainless steel

Materials:

- (1) Stainless steel plunger pin (Aisi 303).
- (2) Stainless steel (Aisi 303) locking indexing plunger body.
- (3) Stainless steel spring (Aisi 301).
- (4) Turned stainless steel lobed knob (Aisi 303).
- (5) Threaded stainless steel lock nut (Aisi 304) (UNI 5589).

Surface finish:

Satin.

Colour:

Natural.

ATTENTION:


- > We recommend an H7 tolerance for the plunger stem bore.
- > The nut is supplied assembled.

Special Requests:

On request the plunger can be supplied completely disassembled.

On request the nut can be supplied disassembled.





Version W738 CIN - with nut

Code	Art.	D	d	H	h	e	s	d2	e2	s2	d1 -0,02-0,04	Q	Weight (g)
W738.0001	W738.I05CIN	18	9	46	16	8	10	M08	13	5	5	5	26
W738.0002	W738.I06CIN	22	11	55	20	10	11	M10	17	6	6	6	71
W738.0003	W738.I08CIN	24	13	66	24	12	14	M12	19	7	8	8	110