

22

KNOB WITH STEEL INDEXING PLUNGER

Coarse pitch indexing plungers - with knob

Materials:

- (1) Stainless steel plunger pin (Aisi 303).
- (3) Stainless steel spring (Aisi 302).
- (4) Reinforced polyamide lobed knob. Cannot be disassembled. Resistant to oils and greases.

W795:

- (2) Indexing plunger body in free-cutting steel.

W795 CIN:

- (2) Stainless steel (Aisi 303) indexing plunger body.

Surface finish:

- (4) Satin.
- (1-2-3) Smooth.

Colour:

- (4) Black (RAL 9011).

W795:

- (2) Galvanised.

W795 CIN:

- (1-2) Natural.


ATTENTION:

- > We recommend an H7 tolerance for the plunger stem bore.

Special Requests:

None.





Version W795 - galvanised steel

Code	Art.	D	d	H	h	e	s	d2	d1 -0,02 -0,04	Q	Weight (g)
W795.0001	W795.J0401	14	7	33	12	6	5	M6	4	4	5
W795.0003	W795.J0501	18	9	42	16	8	6	M8	5	5	11
W795.0005	W795.J0601	22	11	52	20	10	7,5	M10	6	6	23
W795.0007	W795.J0801	24	13	61	24	12	9	M12	8	8	38

Version W795 CIN - stainless steel (Aisi 303)

Code	Art.	D	d	H	h	e	s	d2	d1 -0,02 -0,04	Q	Weight (g)
W795.0002	W795.J0401CIN	14	7	33	12	6	5	M6	4	4	5
W795.0004	W795.J0501CIN	18	9	42	16	8	6	M8	5	5	11
W795.0006	W795.J0601CIN	22	11	52	20	10	7,5	M10	6	6	23
W795.0008	W795.J0801CIN	24	13	61	24	12	9	M12	8	8	38