


H171



08

KNURLED HANDWHEEL WITH SHORT HUB

Knurled handwheels with stud

Materials:

Reinforced polyamide.

Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black (RAL 9011).

Inserts:

H171:

Galvanised steel threaded stud (thread tolerance 6g).


H171CON:

Brass insert with female threaded hole (thread tolerance 6H).

Special requests:

Upon request and for special quantities inserts with stud can be supplied with customised lengths for a minimum quantity of 100 pieces.





Version H171CON: With brass insert.

Code	art.	D	H	d	m	c	d1 6H	Weight (g)
H17125.0002	H17125.TM0601CON	25	12	15.5	4	8	M6	7
H17125.0015	H17125.TM0801CON	25	12	15.5	4	8	M6	8

Version H171: With galvanised steel stud.

Code	art.	D	H	d	m	c	LM	d1 6g	Q	Weight (g)
H17125.0006	H17125.TM06X2001	25	12	15.5	4	8	40	M6	20	11
H17125.0019	H17125.TM08X2001	25	12	15.5	4	8	40	M8	20	15

LM = maximum mouldable length.

Customised stud length available for a minimum of 250 pieces.

08

KNURLED KNOB WITH SLOT END AND THREADED STUD

Knurled handwheels with stud

Materials:

Reinforced polyamide.

Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black (RAL 9011).

Inserts:

Galvanised steel threaded stud (thread tolerance 6g).






BATECO
Copyright ©

Special Requests:

Upon request and for special quantities inserts can be supplied with customised lengths.

Upon request and for special quantities inserts can be supplied in different materials.

Upon request and for special quantities available in the colours indicated in the chart.



BATECO
AN ESSENTIA COMPANY
Copyright ©

Code	art.	D	H	d	m	c	A	B	LM	d16g	Q	Weight (g)
H17220.0003	H17220.TM06X1501	20	8	13,5	1	7	14	2,5	39	M6	15	7

LM = maximum mouldable length.

Threaded stud length on request, with a minimum quantity of 250 pieces.

08

KNURLED SOLID HANDWHEEL WITH THREADED STUD

Knurled handwheels with stud

Materials:

Reinforced polyamide.

Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black (RAL 9011).

Inserts:

Galvanised steel threaded stud (thread tolerance 6g).

Special Requests:


Upon request and for special quantities inserts can be supplied with customised lengths.

Upon request and for special quantities inserts can be supplied in different materials.

Upon request and for special quantities available in the colours indicated in the chart.



BATECO
Copyright ©



BATECO
AN ASSINTRA COMPANY
Copyright ©

Code	art.	D	H	d	m	c	d2	LM	d1 6g	Q	Weight (g)
H75326.0004	H75326.TM05X2001	26	18	16	8.5	9.5	12	50	M5	20	10
H75326.0008	H75326.TM06X2001	26	18	16	8.5	9.5	12	50	M6	20	13
H75326.0009	H75326.TM06X2501	26	18	16	8.5	9.5	12	50	M6	25	14
H75326.0012	H75326.TM08X2001	26	18	16	8.5	9.5	12	50	M8	20	20
H75326.0014	H75326.TM08X3001	26	18	16	8.5	9.5	12	50	M8	30	22

LM = maximum mouldable length.

Threaded stud length on request, with a minimum quantity of 250 pieces.

08

KNURLED SOLID HANDWHEEL WITH FEMALE THREADED INSERT

Knurled handwheels with blind hole

Materials:

Reinforced polyamide.

Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black (RAL 9011).

Inserts:

Brass insert with female threaded hole (thread tolerance 6H).




Special Requests:

Upon request and for special quantities inserts can be supplied in different materials.

Upon request and for special quantities available in the colours indicated in the chart.




BOTECO
AN ESSINTKA COMPANY
Copyright ©



BOTECO
AN ESSINTKA COMPANY
Copyright ©

Code	art.	D	H	d	m	c	d2	d16H	Q	Weight (g)
H75726.0007	H75726.TM0501	26	18	16	8.5	9.5	12	M5	6	9
H75726.0008	H75726.TM0601	26	18	16	8.5	9.5	12	M6	8	10
H75726.0009	H75726.TM0801	26	18	16	8.5	9.5	12	M8	8	11

H758



08

KNURLED HANDWHEEL WITH HUB AND FEMALE THREADED INSERT

Knurled handwheels with blind hole

Materials:

Reinforced polyamide.

Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black (RAL 9011).

Inserts:

Brass insert with female threaded hole (thread tolerance 6H).




Special Requests:

Upon request and for special quantities inserts can be supplied in different materials.

Upon request and for special quantities available in the colours indicated in the chart.



BOTECO
AN ESSENTIA COMPANY
Copyright ©



BOTECO
AN ESSENTIA COMPANY
Copyright ©

Code	art.	D	H	d	m	c	d16H	Q	Weight (g)
H75815.0002	H75815.TM0401	15	11,5	10,5	4	7,5	M4	7	4
H75815.0005	H75815.TM0501	15	11,5	10,5	4	7,5	M5	7	4
H75815.0010	H75815.TM0601	15	11,5	10,5	4	7,5	M6	7	4

08

KNURLED HANDWHEEL WITH HUB AND THREADED STUD

Knurled handwheels with stud

Materials:

Reinforced polyamide.

Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black (RAL 9011).

Inserts:

Galvanised steel threaded stud (thread tolerance 6g).

Special Requests:



Upon request and for special quantities inserts can be supplied with customised lengths.

Upon request and for special quantities inserts can be supplied in different materials.

Upon request and for special quantities available in the colours indicated in the chart.



BATECO
AN ESSENTIA COMPANY
Copyright ©



BATECO
AN ESSENTIA COMPANY
Copyright ©

Code	art.	D	H	d	m	c	LM	d16g	Q	Weight (g)
H75915.0002	H75915.TM03X1101	15	11,5	10,5	4	7,5	70	M3	11	3
H75915.0004	H75915.TM03X2401	15	11,5	10,5	4	7,5	70	M3	24	3,5
H75915.0005	H75915.TM04X1001	15	11,5	10,5	4	7,5	70	M4	10	3,5
H75915.0009	H75915.TM04X2001	15	11,5	10,5	4	7,5	70	M4	20	4
H75915.0014	H75915.TM04X3001	15	11,5	10,5	4	7,5	70	M4	30	4,5
H75915.0020	H75915.TM05X1001	15	11,5	10,5	4	7,5	70	M5	10	4
H75915.0024	H75915.TM05X1601	15	11,5	10,5	4	7,5	70	M5	16	4,5
H75915.0025	H75915.TM05X2001	15	11,5	10,5	4	7,5	70	M5	20	5,5
H75915.0026	H75915.TM05X3001	15	11,5	10,5	4	7,5	70	M5	30	6,5
H75915.0028	H75915.TM06X1001	15	11,5	10,5	4	7,5	70	M6	10	5
H75915.0030	H75915.TM06X1601	15	11,5	10,5	4	7,5	70	M6	16	6
H75915.0032	H75915.TM06X2001	15	11,5	10,5	4	7,5	70	M6	20	7,5

LM = maximum mouldable length.

Threaded stud length on request, with a minimum quantity of 250 pieces.

KNURLED HANDWHEEL WITH THREADED STUD

Knurled handwheels with stud

Il volantino zigrinato piccolo senza mozzo con perno filettato, fa parte della grande famiglia dei volantini zigrinati. Il prodotto è uno dei volantini più piccoli nel catalogo Boteco. Si presenta senza mozzo e con una zigrinatura ideata per avere un ottimo grip usandolo con i polpastrelli della dita. Il volantino zigrinato è ideale per tutte le micro applicazioni ove serve stringere con forza ma con poco spazio. Il campo di utilizzo è universale: attrezzature sportive, attrezzature medicali, illuminazione, macchine per legatoria e cartotecnica, piccoli elettrodomestici, elettroutensili, e tantissime altre. Il volantino zigrinato piccolo senza mozzo H760 è fatto con materiali a base di poliammide rinforzata. Disponibile solo in questa versione, ma previsto anche con mozzo. (volantino zigrinato piccolo con mozzo e inserto filettato e volantino zigrinato piccolo con mozzo e perno filettato, ecc.).

Materials:

Reinforced polyamide.

Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black (RAL 9011).

Inserts:

Galvanised steel threaded stud (thread tolerance 6g).



Special Requests:

Upon request and for special quantities inserts can be supplied with customised lengths.

Upon request and for special quantities inserts can be supplied in different materials.

Upon request and for special quantities available in the colours indicated in the chart.






Code	art.	D	H	LM	d1 6g	Q	Weight (g)
H76015.0004	H76015.TM04X1301	15	8	77	M4	13	2
H76015.0005	H76015.TM04X1501	15	8	77	M4	15	2
H76015.0009	H76015.TM04X1901	15	8	77	M4	19	2,5
H76015.0012	H76015.TM04X2401	15	8	77	M4	24	3
H76015.0021	H76015.TM05X1501	15	8	77	M5	15	4
H76015.0026	H76015.TM05X1901	15	8	77	M5	19	4,5
H76015.0027	H76015.TM05X2401	15	8	77	M5	24	5
H76015.0029	H76015.TM05X2901	15	8	77	M5	29	5,5
H76015.0035	H76015.TM06X1501	15	8	77	M6	15	5,5
H76015.0039	H76015.TM06X1901	15	8	77	M6	19	6,5
H76015.0042	H76015.TM06X2401	15	8	77	M6	24	7
H76015.0043	H76015.TM06X2901	15	8	77	M6	29	7,5

LM = maximum mouldable length.

Threaded stud length on request, with a minimum quantity of 250 pieces.

H765



08

KNURLED HOLLOW HANDWHEEL WITH THREADED THROUGH-HOLE INSERT

Knurled handwheels with through hole

Materials:

Reinforced polyamide.

Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black (RAL 9011).

Inserts:

H765:

Brass insert with threaded through hole (thread tolerance 6H).

H765PIN:

Stainless steel insert with threaded through hole (Aisi 303) (thread tolerance 6H).

Special Requests:


Upon request and for special quantities available in the colours indicated in the chart.




BATECO
BY BATECO GROUP
Copyright ©




BATECO
BY BATECO GROUP
Copyright ©



Version H765: brass insert.

Code	art.	D	H	d	m	c	d2	d3	d4	h3	d16H	Q	Weight (g)
H76515.0002	H76515.TM0401	15	10.5	10	4.5	6	8	10	7.5	2	M4	8.5	2
H76515.0006	H76515.TM0501	15	10.5	10	4.5	6	8	10	7.5	2	M5	8.5	2
H76521.0002	H76521.TM0501	21	15	13	6.5	8.5	9.5	15	10.5	2.5	M5	12.5	5
H76521.0006	H76521.TM0601	21	15	13	6.5	8.5	9.5	15	10.5	2.5	M6	12.5	5
H76526.0002	H76526.TM0601	26	18	16	8.5	9.5	12	19	13	3	M6	15	10
H76526.0004	H76526.TM0801	26	18	16	8.5	9.5	12	19	13	3	M8	15	10
H76533.0002	H76533.TM0801	32	23	20	10.5	12.5	15	23	16	5	M8	18	16
H76533.0004	H76533.TM1001	32	23	20	10.5	12.5	15	23	16	5	M10	18	16
H76540.0002	H76540.TM0801	40	28	25	12.5	15.5	18	29	20,5	6	M8	22	31
H76540.0004	H76540.TM1001	40	28	25	12.5	15.5	18	29	20,5	6	M10	22	32
H76540.0006	H76540.TM1201	40	28	25	12.5	15.5	18	29	20,5	6	M12	22	32
H76540.0008	H76540.TM1401	40	28	25	12.5	15.5	18	29	20,5	6	M14	22	34

Version H765PIN: stainless steel insert Aisi 303.

Code	art.	D	H	d	m	c	d2	d3	d4	h3	d16H	Q	Weight (g)
H76515.0003	H76515.TM0401PIN	15	10.5	10	4.5	6	8	10	7.5	2	M4	8.5	3
H76515.0007	H76515.TM0501PIN	15	10.5	10	4.5	6	8	10	7.5	2	M5	8.5	3
H76521.0003	H76521.TM0501PIN	21	15	13	6.5	8.5	9.5	15	10.5	2.5	M5	12.5	6
H76521.0007	H76521.TM0601PIN	21	15	13	6.5	8.5	9.5	15	10.5	2.5	M6	12.5	6
H76526.0003	H76526.TM0601PIN	26	18	16	8.5	9.5	12	19	13	3	M6	15	11.5

Code	art.	D	H	d	m	c	d2	d3	d4	h3	d1 6H	Q	Weight (g)
H76526.0005	H76526.TM0801PIN	26	18	16	8.5	9.5	12	19	13	3	M8	15	11.5
H76533.0003	H76533.TM0801PIN	32	23	20	10.5	12.5	15	23	16	5	M8	18	18
H76533.0005	H76533.TM1001PIN	32	23	20	10.5	12.5	15	23	16	5	M10	18	18
H76540.0003	H76540.TM0801PIN	40	28	25	12.5	15.5	18	29	20,5	6	M8	22	32
H76540.0005	H76540.TM1001PIN	40	28	25	12.5	15.5	18	29	20,5	6	M10	22	31
H76540.0007	H76540.TM1201PIN	40	28	25	12.5	15.5	18	29	20,5	6	M12	22	34

08

KNURLED HOLLOW HANDWHEEL WITH THREADED STUD

Knurled handwheels with stud

Materials:

Reinforced polyamide.

Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black (RAL 9011).

Inserts:



Galvanised steel threaded stud (thread tolerance 6g).

Special Requests:

Upon request and for special quantities inserts can be supplied with customised lengths.

Upon request and for special quantities inserts can be supplied in different materials.

Upon request and for special quantities available in the colours indicated in the chart.



Code	art.	D	H	d	m	c	d2	d3	d4	h1	h3	LM	d1 6g	Q	Weight (g)
H76615.0001	H76615.TM04X1101	15	10.5	10	4.5	6	8	10	7.5	8.5	2	40	M4	11	2,5
H76615.0004	H76615.TM04X1501	15	10.5	10	4.5	6	8	10	7.5	8.5	2	40	M4	15	3
H76615.0007	H76615.TM04X1901	15	10.5	10	4.5	6	8	10	7.5	8.5	2	40	M4	19	3,5
H76615.0013	H76615.TM05X1101	15	10.5	10	4.5	6	8	10	7.5	8.5	2	40	M5	11	4
H76615.0016	H76615.TM05X1501	15	10.5	10	4.5	6	8	10	7.5	8.5	2	40	M5	15	4,5
H76615.0018	H76615.TM05X1901	15	10.5	10	4.5	6	8	10	7.5	8.5	2	40	M5	19	5
H76621.0003	H76621.TM05X1001	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	40	M5	10	6,5
H76621.0005	H76621.TM05X1601	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	40	M5	16	6,5
H76621.0007	H76621.TM05X2001	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	40	M5	20	7,5
H76621.0011	H76621.TM05X3001	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	40	M5	30	9,5
H76621.0015	H76621.TM06X1001	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	40	M6	10	7,5
H76621.0022	H76621.TM06X1601	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	40	M6	16	8,5
H76621.0024	H76621.TM06X2001	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	40	M6	20	9
H76621.0029	H76621.TM06X2501	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	40	M6	25	10,5
H76626.0002	H76626.TM06X1001	26	18	16	8.5	9.5	12	19	13	15	3	80	M6	10	10
H76626.0006	H76626.TM06X1601	26	18	16	8.5	9.5	12	19	13	15	3	80	M6	16	11
H76626.0009	H76626.TM06X2001	26	18	16	8.5	9.5	12	19	13	15	3	80	M6	20	11,5
H76626.0012	H76626.TM06X2501	26	18	16	8.5	9.5	12	19	13	15	3	80	M6	25	12,5
H76626.0029	H76626.TM08X1601	26	18	16	8.5	9.5	12	19	13	15	3	80	M8	16	15,5
H76626.0031	H76626.TM08X2001	26	18	16	8.5	9.5	12	19	13	15	3	80	M8	20	16,5
H76626.0034	H76626.TM08X2501	26	18	16	8.5	9.5	12	19	13	15	3	80	M8	25	18,5
H76633.0005	H76633.TM08X1601	32	23	20	10.5	12.5	15	23	16	18	5	80	M8	16	21
H76633.0008	H76633.TM08X2001	32	23	20	10.5	12.5	15	23	16	18	5	80	M8	20	24
H76633.0013	H76633.TM08X3001	32	23	20	10.5	12.5	15	23	16	18	5	80	M8	30	30
H76633.0022	H76633.TM10X2001	32	23	20	10.5	12.5	15	23	16	18	5	80	M10	20	30
H76633.0025	H76633.TM10X3001	32	23	20	10.5	12.5	15	23	16	18	5	80	M10	30	30,5
H76633.0026	H76633.TM10X4001	32	23	20	10.5	12.5	15	23	16	18	5	80	M10	40	35,5
H76640.0003	H76640.TM08X1601	40	28	25	12.5	15.5	18	29	20,5	22	6	100	M8	16	29,5
H76640.0005	H76640.TM08X3001	40	28	25	12.5	15.5	18	29	20,5	22	6	100	M8	30	38
H76640.0006	H76640.TM08X4001	40	28	25	12.5	15.5	18	29	20,5	22	6	100	M8	40	44
H76640.0011	H76640.TM10X3001	40	28	25	12.5	15.5	18	29	20,5	22	6	100	M10	30	46
H76640.0019	H76640.TM12X5001	40	28	25	12.5	15.5	18	29	20,5	22	6	100	M12	50	78

LM = maximum mouldable length.

Threaded stud length on request, with a minimum quantity of 250 pieces.

08

KNURLED HOLLOW HANDWHEEL WITH STAINLESS STEEL THREADED STUD

Knurled handwheels with stud

Materials:

Reinforced polyamide.

Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black (RAL 9011).

Inserts:

Stainless steel threaded stud (Aisi 303) (thread tolerance 6g).


Special Requests:

Upon request and for special quantities inserts can be supplied with customised lengths.

Upon request and for special quantities available in the colours indicated in the chart.



BOTECO
Copyright ©



BOTECO
AN ESSENTIA COMPANY
Copyright ©

Code	art.	D	H	d	m	c	d2	d3	d4	h1	h3	LM	d1 6g	Q	Weight (g)
H76615.0017	H76615.TM05X1501CIN	15	10.5	10	4.5	6	8	10	7.5	8.5	2	40	M5	15	-
H76621.0006	H76621.TM05X1601CIN	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	40	M5	16	9.5
H76621.0019	H76621.TM06X1501CIN	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	40	M6	15	-
H76626.0010	H76626.TM06X2001CIN	26	18	16	8.5	9.5	12	19	13	15	3	80	M6	20	-
H76626.0032	H76626.TM08X2001CIN	26	18	16	8.5	9.5	12	19	13	15	3	80	M8	20	16.5
H76633.0017	H76633.TM08X4001CIN	32	23	20	10.5	12.5	15	23	16	18	5	80	M8	40	36
H76640.0009	H76640.TM10X2001CIN	40	28	25	12.5	15.5	18	29	20,5	22	6	100	M10	20	-
H76640.0018	H76640.TM12X3001CIN	40	28	25	12.5	15.5	18	29	20,5	22	6	100	M12	30	-

LM = maximum mouldable length.

Threaded stud length on request, with a minimum quantity of 250 pieces.

08

KNURLED HOLLOW HANDWHEEL WITH FEMALE THREADED INSERT

Knurled handwheels with blind hole

Il volantino zigrinato con inserto filettato, è il più famoso modello zigrinato nel catalogo Boteco. Un pomello ideato per essere manovrato con le dita e non con la mano intera. Infatti, il progetto prevede una geometria di zigrinatura diversa dalla concorrenza, la quale offre un ottimo grip per le dita che permette di imprimere un'ottima forza di serraggio nonostante le piccole dimensioni. La linea prevede diversi diametri e versioni e può essere venduto con ottimi prezzi grazie agli stampi progettati per grandi quantità. Il campo di utilizzo è universale: attrezzature sportive, attrezzature medicali, illuminazione, macchine per legatoria e cartotecnica, piccoli elettrodomestici, elettroutensili, macchine utensili, arrendamento industriale, macchine per imballaggio, attrezzature per alimenti, e tantissime altre. Il volantino zigrinato con inserto filettato H767 è fatto con materiali a base di poliammide rinforzata. Disponibile anche in altre versioni con foro passante e perno filettato. (volantino zigrinato con foro filettato passante, volantino zigrinato con perno, volantini con inserti filettati in acciaio inossidabile, ecc.).

Materials:

Reinforced polyamide.

Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black (RAL 9011).

Inserts:

Brass insert with female threaded hole (thread tolerance 6H).


Special Requests:

Upon request and for special quantities inserts can be supplied in different materials.

Upon request and for special quantities available in the colours indicated in the chart.



BOTECO
Copyright ©



BOTELO
AN ESSENTIA COMPANY
Copyright ©

Code	art.	D	H	d	m	c	d2	d3	d4	h1	h3	d16H	Q	Weight (g)
H76721.0002	H76721.TM0501	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	M5	7	5.5
H76721.0005	H76721.TM0601	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	M6	7	6
H76726.0002	H76726.TM0601	26	18	16	8.5	9.5	12	19	13	15	3	M6	8	8
H76726.0005	H76726.TM0801	26	18	16	8.5	9.5	12	19	13	15	3	M8	8	8.5
H76733.0002	H76733.TM0801	32	23	20	10.5	12.5	15	23	16	18	5	M8	11	15.5
H76733.0004	H76733.TM1001	32	23	20	10.5	12.5	15	23	16	18	5	M10	10	16
H76740.0001	H76740.TM0801	40	28	25	12.5	15.5	18	29	20,5	22	6	M8	14	27
H76740.0002	H76740.TM1001	40	28	25	12.5	15.5	18	29	20,5	22	6	M10	14	28
H76740.0003	H76740.TM1201	40	28	25	12.5	15.5	18	29	20,5	22	6	M12	12	29

H770



08

KNURLED KNOB WITH FEMALE THREADED INSERT

Knurled handwheels with blind hole

Materials:

Reinforced polyamide.

Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black (RAL 9011).


Inserts:

Brass insert with female threaded hole (thread tolerance 6H).

Special Requests:

Upon request and for special quantities inserts can be supplied in different materials.

Upon request and for special quantities available in the colours indicated in the chart.



Code	art.	D	H	d	m	c	d3	h3	d1 6H	Q	Weight (g)
H77018.0001	H77018.TM0401	17.5	17.5	12	4	13.5	9	5	M4	7	5

Code	art.	D	H	d	m	c	d3	h3	d1 6H	Q	Weight (g)
H77018.0002	H77018.TM0501	17.5	17.5	12	4	13.5	9	5	M5	7	5
H77018.0003	H77018.TM0601	17.5	17.5	12	4	13.5	9	5	M6	7	5

08

KNURLED KNOB WITH THREADED STUD

Knurled handwheels with stud

Materials:

Reinforced polyamide.

Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black (RAL 9011).

Inserts:

Galvanised steel threaded stud (thread tolerance 6g).

Special Requests:


Upon request and for special quantities inserts can be supplied with customised lengths.

Upon request and for special quantities inserts can be supplied in different materials.

Upon request and for special quantities available in the colours indicated in the chart.



BATECO
AN ELLIPTICA COMPANY
Copyright ©



BATECO
AN ELLIPTICA COMPANY
Copyright ©

Code	art.	D	H	d	m	c	d3	h3	LM	d1 6g	Q	Weight (g)
H77118.0001	H77118.TM04X1001	17.5	17.5	12	4	13.5	9	5	50	M4	10	6
H77118.0005	H77118.TM04X1601	17.5	17.5	12	4	13.5	9	5	50	M4	16	6,5
H77118.0008	H77118.TM04X3001	17.5	17.5	12	4	13.5	9	5	50	M4	30	8
H77118.0010	H77118.TM05X1001	17.5	17.5	12	4	13.5	9	5	60	M5	10	6,5
H77118.0012	H77118.TM05X1601	17.5	17.5	12	4	13.5	9	5	60	M5	16	7
H77118.0013	H77118.TM05X2001	17.5	17.5	12	4	13.5	9	5	60	M5	20	8
H77118.0024	H77118.TM06X1601	17.5	17.5	12	4	13.5	9	5	60	M6	16	8,5
H77118.0026	H77118.TM06X2001	17.5	17.5	12	4	13.5	9	5	60	M6	20	9

LM = maximum mouldable length.

Threaded stud length on request, with a minimum quantity of 250 pieces.

08

KNURLED KNOB WITH THREADED THROUGH-HOLE INSERT

Knurled handwheels with through hole

Materials:

Reinforced polyamide.

Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black (RAL 9011).

Inserts:

Brass insert with threaded through hole (thread tolerance 6H).


Special Requests:

Upon request and for special quantities inserts can be supplied in different materials.

Upon request and for special quantities available in the colours indicated in the chart.



BOTECO
Copyright ©



BOTECO
AN ESSENTIA COMPANY
Copyright ©

Code	art.	D	H	d	m	c	d3	h3	d1 6H	Q	Weight (g)
H77218.0001	H77218.TM0401	17.5	17.5	12	4	13.5	9	4.5	M4	13	5.5

Code	art.	D	H	d	m	c	d3	h3	d16H	Q	Weight (g)
H77218.0002	H77218.TM0501	17.5	17.5	12	4	13.5	9	4.5	M5	13	5.5
H77218.0003	H77218.TM0601	17.5	17.5	12	4	13.5	9	4.5	M6	13	5.5

H773



08

KNURLED KNOB WITH SLOT END AND FEMALE THREADED INSERT

Knurled handwheels with blind hole

Materials:

Reinforced polyamide.

Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black (RAL 9011).

Inserts:

Brass insert with female threaded hole (thread tolerance 6H).


Special Requests:

Upon request and for special quantities inserts can be supplied in different materials.

Upon request and for special quantities available in the colours indicated in the chart.



BOTECO
AN ESSENTIA COMPANY
Copyright ©



BOTECO
AN ESSENTIA COMPANY
Copyright ©

Code	art.	D	H	d	m	c	A	B	d16H	Q	Weight (g)
H77318.0001	H77318.TM0401	17.5	18	12	4	14	1.2	1.5	M4	7	6.5
H77318.0002	H77318.TM0501	17.5	18	12	4	14	1.2	1.5	M5	7	7
H77318.0003	H77318.TM0601	17.5	18	12	4	14	1.2	1.5	M6	7	7

08

KNURLED KNOB WITH SLOT END AND THREADED STUD

Knurled handwheels with stud

Materials:

Reinforced polyamide.

Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black (RAL 9011).

Inserts:

Galvanised steel threaded stud (thread tolerance 6g).

Special Requests:


Upon request and for special quantities inserts can be supplied with customised lengths.

Upon request and for special quantities inserts can be supplied in different materials.

Upon request and for special quantities available in the colours indicated in the chart.



BATECO
AN ESSENTIA COMPANY
Copyright ©




BATECO
AN ESSENTIA COMPANY
Copyright ©

Code	art.	D	H	d	m	c	A	B	LM	d1 6g	Q	Weight (g)
H77418.0003	H77418.TM04X3001	17.5	18	12	4	14	1.2	1.5	50	M4	30	7.5
H77418.0006	H77418.TM05X3001	17.5	18	12	4	14	1.2	1.5	60	M5	30	9
H77418.0009	H77418.TM06X3001	17.5	18	12	4	14	1.2	1.5	60	M6	30	11

LM = maximum mouldable length.

Threaded stud length on request, with a minimum quantity of 250 pieces.

W459HIN



Aisi
304



08

STAINLESS STEEL KNURLED KNOB WITH THREADED HOLE

Metal knurled handwheels

Materials:

Precision-cast stainless steel, (Aisi 304).

Surface finish:

Electropolished satin finish.

Colour:

Natural.

Hole:




Female threaded hole (thread tolerance 6H).

Special requests:

None.



BOTELCO
AN ESSENTIA COMPANY
Copyright ©



BOTELCO
AN ESSENTIA COMPANY
Copyright ©

Code	Art.	D	H	d	m	d16H	Q	Weight (g)
W459020.0001	W459020.HNM05HIN	20	13	14	4,5	M5	8	3
W459024.0001	W459024.HNM06HIN	24	15	16	4,5	M6	9	3
W459028.0001	W459028.HNM08HIN	28	17	18	4,5	M8	10	3

08

STAINLESS STEEL KNURLED KNOB WITH THREADED STUD

Metal knurled handwheels

Materials:

Knob:

Precision-cast stainless steel, (Aisi 304).

Stud:

Stainless steel (Aisi 303).

Surface finish:

Knob:

Electropolished satin finish.

Stud:

Smooth.

Colour:

Natural.

Inserts:


Turned threaded stud (thread tolerance 6g).

ATTENTION: The stud is fixed with glue.

Special requests:

Upon request and for a minimum of 50 pieces inserts can be supplied with customised lengths.





Code	Art.	D	H	d	m	d1	Q	Weight (g)
W460020.0001	W460020.HNM05X20HIN	20	13	14	4,5	M5	20	3
W460024.0002	W460024.HNM06X20HIN	24	15	16	4,5	M6	20	3
W460028.0001	W460028.HNM08X30HIN	28	17	18	4,5	M8	30	3

Customised stud length available for a minimum of 50 pieces.

08

KNURLED METAL HANDWHEEL WITH THREADED STUD

Metal knurled handwheels

Materials:

W464:

Steel with strength class 5.8.

W464CIN:

Stainless steel (Aisi 303).

Surface finish:

Turned with low roughness.

Colour:

W464:

Nickel plated (galvanic treatment).

W464 CIN:

Natural.

Alternative finishes:

Black-oxide treatment:

(replace the final letter of the code (H) with letter B
(W46429.SM08X..B).

Galvanising:

(replace the final letter of the code (H) with letter Z
(W46429.SM08X..Z).


Stud:

Threaded stud machined from solid metal (thread tolerance 6g).

Special requests:

Upon request and for special quantities inserts can be supplied
with customised lengths.





Version W464 - nickel-plated steel

Code	Art.	d	D	H	m	c	Q Max	d1 6g	Q	Weight (g)
W46411.0006	W46411.SM03X16H	6	11	8	5	3	16	M3	16	5
W46415.0002	W46415.SM04X10H	8	15	10	6	4	20	M4	10	7.8
W46419.0005	W46419.SM05X16H	10	19	12	8	4	25	M5	16	15,6
W46423.0005	W46423.SM06X16H	12	23	15	10	5	35	M6	16	27,5
W46423.0010	W46423.SM06X35H	12	23	15	10	5	35	M6	35	30,5
W46429.0004	W46429.SM08X16H	16	29	18	12	6	40	M8	16	55
W46429.0007	W46429.SM08X30H	16	29	18	12	6	40	M8	30	59
W46435.0004	W46435.SM10X25H	20	35	23	15	8	40	M10	25	109.5

Customised stud length available for a minimum of 100 pieces.

Qmax = maximum turning length.

Version W464 CIN - stainless steel (Aisi 303)

Code	Art.	d	D	H	m	c	Q Max	d1 6g	Q	Weight (g)
W46423.0002	W46423.IM06X35CIN	12	23	15	10	5	35	M6	35	30.5

Customised stud length available for a minimum of 100 pieces.

Qmax = maximum turning length.

08

KNURLED METAL HANDWHEEL WITH THREADED HOLE

Metal knurled handwheels

Materials:

W466:

Steel with strength class 5.8.

W466 PIN:

Stainless steel (Aisi 303).

Surface finish:

Turned with low roughness.

Colour:

W466:

Nickel plated (galvanic treatment).

W466PIN:

Natural.

Alternative finishes:

Black-oxide treatment:

(replace the final letter of the code (H) with letter B (W46629.SM08B).

Galvanising:

(replace the final letter of the code (H) with letter Z (W46629.SM08Z).

Hole:

Threaded through hole machined from solid metal (thread tolerance 6H).


Special requests:

Upon request and for special quantities inserts can be supplied to customer's drawing with hole diameter d1.





BOTECOA
AN ESSENTIA COMPANY
Copyright ©



BOTECOA
AN ESSENTIA COMPANY
Copyright ©

Version W466 - nickel-plated steel

Code	Art.	d	D	H	m	c	d1 6H	Weight (g)
W46611.0003	W46611.SM03H	6	11	8	5	3	M3	3
W46615.0003	W46615.SM04H	8	15	10	6	4	M4	7
W46619.0002	W46619.SM05H	10	19	12	8	4	M5	12
W46623.0004	W46623.SM06H	12	23	15	10	5	M6	22.5
W46629.0003	W46629.SM08H	16	29	18	12	6	M8	45
W46635.0003	W46635.SM10H	20	35	23	15	8	M10	87
W46639.0004	W46639.SM12H	22	39	25	15	10	M12	121

Version W466 PIN - stainless steel (Aisi 303)

Code	Art.	d	D	H	m	c	d16H	Weight (g)
W46611.0001	W46611.IM03PIN	6	11	8	5	3	M3	3
W46615.0001	W46615.IM04PIN	8	15	10	6	4	M4	7
W46619.0001	W46619.IM05PIN	10	19	12	8	4	M5	12
W46623.0001	W46623.IM06PIN	12	23	15	10	5	M6	22.5
W46629.0001	W46629.IM08PIN	16	29	18	12	6	M8	45
W46635.0001	W46635.IM10PIN	20	35	23	15	8	M10	87
W46639.0002	W46639.IM12PIN	22	39	25	15	10	M12	121

08

KNURLED METAL HANDWHEEL WITH SHORT HUB AND THREADED HOLE

Metal knurled handwheels

Materials:

W467:

Steel with strength class 5.8.

W467 PIN:

Stainless steel (Aisi 303).

Surface finish:

Turned with low roughness.

Colour:

W467:

Nickel plated (galvanic treatment).

W467 PIN:

Natural.

Alternative finishes:

Black-oxide treatment:

(replace the final letter of the code (H) with letter B
(W46729.SM08B).

Galvanising:

(replace the final letter of the code (H) with letter Z
(W46729.SM08Z).

Hole:


Threaded through hole machined from solid metal (thread
tolerance 6H).

Special requests:

Upon request and for special quantities inserts can be supplied
to customer's drawing with hole diameter d1.



BOTEC
Copyright ©



Version W467 - nickel-plated steel

Code	Art.	d	D	H	m	c	d1 6H	Weight (g)
W46711.0002	W46711.SM03H	6	11	3	0,5	3	M3	2
W46715.0002	W46715.SM04H	8	15	4	0,5	4	M4	5
W46719.0002	W46719.SM05H	10	19	5	1	4	M5	9
W46723.0002	W46723.SM06H	12	23	6	1	5	M6	16
W46729.0002	W46729.SM08H	16	29	8	2	6	M8	32
W46735.0003	W46735.SM10H	20	35	10	2	8	M10	61
W46739.0002	W46739.SM12H	22	39	12	2	10	M12	92

Version W467 PIN - stainless steel (Aisi 303)

Code	Art.	d	D	H	m	c	d1 6H	Weight (g)
W46711.0001	W46711.IM03PIN	6	11	3	0,5	3	M3	2
W46715.0001	W46715.IM04PIN	8	15	4	0,5	4	M4	5
W46719.0001	W46719.IM05PIN	10	19	5	1	4	M5	9
W46723.0001	W46723.IM06PIN	12	23	6	1	5	M6	16
W46729.0001	W46729.IM08PIN	16	29	8	2	6	M8	32
W46735.0001	W46735.IM10PIN	20	35	10	2	8	M10	61
W46739.0001	W46739.IM12PIN	22	39	12	2	10	M12	92

08

DIN 6303 - KNURLED THUMB KNOB WITH THREADED HOLE

Metal knurled handwheels

Materials:

Y303:

Free-cutting steel.

Y303PIN:

Stainless steel (Aisi 303).

Surface finish:

Smooth, turned.

Colour:

Y303:

Black-oxide treatment.

Y303PIN:

Natural.

Hole:


Threaded through hole (thread tolerance 6H).

Special requests:

None.



BOTECOA
AN ESSENTIA COMPANY
Copyright ©



BOTECOA
AN ESSENTIA COMPANY
Copyright ©

Version Y303: black-oxide treated steel

Code	Art.	D	d	H	m	c	d16H	Q	Weight (g)
Y303020.0002	Y303020.VBM05	20	14	12	4	8	M5	7	17
Y303024.0002	Y303024.VBM06	24	16	14	4	10	M6	8	30
Y303030.0002	Y303030.VBM08	30	20	17	5	12	M8	10	50
Y303036.0002	Y303036.VBM10	36	28	20	6	14	M10	12	90
Y303040.0002	Y303040.VBM12	40	32	24	8	16	M12	16	124

Version Y303 PIN: stainless steel (Aisi 303)

Code	Art.	D	d	H	m	c	d16H	Q	Weight (g)
Y303020.0001	Y303020.INM05PIN	20	14	12	4	8	M5	7	17
Y303024.0001	Y303024.INM06PIN	24	16	14	4	10	M6	8	30
Y303030.0001	Y303030.INM08PIN	30	20	17	5	12	M8	10	50
Y303036.0001	Y303036.INM10PIN	36	28	20	6	14	M10	12	90
Y303040.0001	Y303040.INM12PIN	40	32	24	8	16	M12	16	124

Y653



08

DIN 653 - FULL STEEL DIAMOND KNURLED THUMB SCREW WITH THREADED DOME-END STUD

Metal knurled handwheels

Materials:

Y653:

Free-cutting steel.

Y653 CIN:

Stainless steel (Aisi 303).

Surface finish:

Smooth, turned.

Colour:

Y653:

Black-oxide treatment.

Y653 CIN:

Natural.

Stud:


Threaded stud with dome end (thread tolerance 6g).

Special requests:

None.



BOTELCO
AN ESSENTIA COMPANY
Copyright ©



BOTELCO
AN ESSENTIA COMPANY
Copyright ©

Version Y653: black-oxide treated steel

Code	art.	D	H	d1 6g	Q	Weight (g)
Y653012.0004	Y653012.VBM03X06	12	2,5	M3	06	3
Y653012.0005	Y653012.VBM03X10	12	2,5	M3	10	3
Y653016.0003	Y653016.VBM04X10	16	3,5	M4	10	6
Y653016.0004	Y653016.VBM04X16	16	3,5	M4	16	7
Y653020.0004	Y653020.VBM05X10	20	4	M5	10	11
Y653020.0005	Y653020.VBM05X16	20	4	M5	16	12
Y653020.0006	Y653020.VBM05X25	20	4	M5	25	14
Y653024.0007	Y653024.VBM06X12	24	5	M6	12	20
Y653024.0008	Y653024.VBM06X16	24	5	M6	16	21
Y653024.0009	Y653024.VBM06X25	24	5	M6	25	23
Y653024.0010	Y653024.VBM06X30	24	5	M6	30	24
Y653024.0011	Y653024.VBM06X35	24	5	M6	35	25
Y653030.0006	Y653030.VBM08X16	30	6	M8	16	37
Y653030.0007	Y653030.VBM08X20	30	6	M8	20	39
Y653030.0008	Y653030.VBM08X25	30	6	M8	25	40
Y653030.0009	Y653030.VBM08X35	30	6	M8	35	43
Y653030.0010	Y653030.VBM08X40	30	6	M8	40	48
Y653036.0004	Y653036.VBM10X20	36	8	M10	20	72
Y653036.0005	Y653036.VBM10X30	36	8	M10	30	76
Y653036.0006	Y653036.VBM10X40	36	8	M10	40	80

Version Y653CIN - stainless steel (Aisi 303)

Code	art.	D	H	d1 6g	Q	Weight (g)
Y653012.0001	Y653012.INM03X06CIN	12	2,5	M3	06	3
Y653012.0002	Y653012.INM03X10CIN	12	2,5	M3	10	3
Y653016.0001	Y653016.INM04X10CIN	16	3,5	M4	10	6
Y653016.0002	Y653016.INM04X16CIN	16	3,5	M4	16	7
Y653020.0001	Y653020.INM05X10CIN	20	4	M5	10	11
Y653020.0002	Y653020.INM05X16CIN	20	4	M5	16	12
Y653020.0003	Y653020.INM05X25CIN	20	4	M5	25	14
Y653024.0001	Y653024.INM06X12CIN	24	5	M6	12	20
Y653024.0002	Y653024.INM06X16CIN	24	5	M6	16	21
Y653024.0003	Y653024.INM06X25CIN	24	5	M6	25	23
Y653024.0004	Y653024.INM06X30CIN	24	5	M6	30	24
Y653024.0005	Y653024.INM06X35CIN	24	5	M6	35	25
Y653030.0001	Y653030.INM08X16CIN	30	6	M8	16	37
Y653030.0002	Y653030.INM08X20CIN	30	6	M8	20	39
Y653030.0003	Y653030.INM08X25CIN	30	6	M8	25	40
Y653030.0004	Y653030.INM08X35CIN	30	6	M8	35	43

Code	art.	D	H	d16g	Q	Weight (g)
Y653030.0005	Y653030.INM08X40CIN	30	6	M8	40	48
Y653036.0001	Y653036.INM10X20CIN	36	8	M10	20	72
Y653036.0002	Y653036.INM10X30CIN	36	8	M10	30	76
Y653036.0003	Y653036.INM10X40CIN	36	8	M10	40	80